### N 90, Built-in oven, Stainless steel B58CT68H0B







#### Included accessories

1 x combination grid, 1 x universal pan

#### Optional accessories

Z11AB15A0 : Baking tray, non-stick ceramic coated , Z11CR10X0 : Baking and roasting grid (standard) , Z11GT10X3 : Glass roasting dish, 5,4l , Z11GU20X0 : Glasspan , Z11SZ00X0 : SeamlessCombination mounting kit , Z11SZ80X0 : SeamlessCombination 60 + 29cm , Z11SZ90X0 : SeamlessCombination 60 + 45cm , Z11TC10X0 : ComfortFlex Rail (1 level) , Z12CB10A0 : Baking tray, anthracite enamelled , Z12CM10A0 : Moussaka pan, anthracite enamelled , Z12CQ10A0 : Grill tray, anthracite enamelled , Z18C60X0 : Cookbook , Z1913X0 : Baking Stone

# Built-in oven with SLIDE&HIDE<sup>®</sup> - unrestricted access to the oven interior

- $\sqrt{\rm Slide \& Hide ^{\odot}}$  unrestricted access in the oven interior and easy handling due to rotating handle
- $\checkmark\,$  Dual cleaning options:
- $\checkmark\,$  Pyrolytic cleaning programmes just let the oven interior clean itself.
- $\checkmark$  EasyClean the quick and easy option for day to day maintenance.
- √ FullTouch Control simple, precise oven control by fingertip touch on the smooth surface of the high resolution TFT colour display.
- $\checkmark\,$  Home Connect rediscover your kitchen with our connected home appliances, from wherever you are.

#### Features

V

#### Technical Data

Color / Material Front : Stainless steel Construction type : Built-in Integrated Cleaning system : Hydrolytic, Pyrolytic Required niche size for installation (HxWxD) : 585-595 x 560-568 x 550 Dimensions of the product (mm) : 595 x 596 x 548 Dimensions of the packed product (HxWxD) (mm) : 670 x 690 x 660 Control Panel Material : Stainless steel Door Material : Glass Net weight (kg): 42.306 Usable volume of cavity (I) : 71 Cooking method : , 4D hot air, Bottom heat, Bread Baking Setting, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air-Eco, Hot air grilling, low temperature cooking, Pizza setting, pre-heating, warming First cavity material : Enamelled Temperature control : electronic Number of interior lights : 3 Approval certificates : CE, VDE Length of electrical supply cord (cm) : 120 EAN code : 4242004236085 Number of cavities (2010/30/EC) : 1 Energy efficiency class (2010/30/EC) : A Energy consumption per cycle conventional (2010/30/EC) : 0.90 Energy consumption per cycle forced air convection (2010/30/EC) : 0.74 Energy efficiency index (2010/30/EC) : 87.1 Connection rating (W): 3450 Current (A) : 16 Voltage (V) : 220-240 Frequency (Hz) : 50; 60 Plug type : no plug



## N 90, Built-in oven, Stainless steel B58CT68H0B

#### Features

#### Design

- 5.7" TFT colour and graphics display with FullTouch control
- Touch control
- Cavity inner surface: Enamel anthracite
- Slide&Hide<sup>®</sup> with rotating handle

#### Features

- HomeConnect ready on WLAN
- Control panel lock Automatic safety switch off Residual heat indicator Start button Door contact switch
- Temperature proposal Actual temperature display Heating up indicator Sabbath setting
- MultiPoint MeatProbe
- Baking and roasting assistant
- NeffLight (2 x 20 Watt halogen lamps) , LED light
- Quadruple glazed door

#### Cleaning

- Pyrolytic cleaning
- EasyClean
- Full glass inner door

#### Programmes/functions

- 15 heating methods: CircoTherm<sup>®</sup>, CircoTherm<sup>®</sup> Gentle, Top/ bottom heat, Conventional heat Gentle, Hot air grilling, Full surface grill, Centre surface grill, CircoTherm<sup>®</sup> intensive, Bread baking, Bottom heat, Low temperature cooking, Defrost, Dough proving, Plate warming, Keep warm
- Rapid heat
- Cooling fan
- Accessories
- 1-level flexible telescopic rail, full extension, Stop function
- 1 x combination grid, 1 x universal pan


#### Performance/technical information

- Energy efficiency rating (acc. EU Nr. 65/2014): A Energy consumption per cycle in conventional mode: 0.9 kwh Energy consumption per cycle in fan-forced convection mode: 0.74 kwh
- Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre
- Total connected load electric: 3.45 KW
- Temperature range 40 °C 275 °C
- Length of mains cable: 120 cm
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 596 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual

## N 90, Built-in oven, Stainless steel B58CT68H0B

### Dimensioned drawings

Installation with a hob.



measurements in mm

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm

