
N 50, Built-in oven, Stainless steel B5ACM7HN0B



COOKING PASSION SINCE 1877





Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated

Z11CB10E0 Baking tray, grey enamelled

Z11CR10X0 Baking and roasting grid (standard)

Z11GT10X3 Glass roasting dish, 5,4l

Z11TF36X0 3 level telescopic rails, full ext

Z11TI15X0 Cliprails

Z13CV05S0 Cover Strip Z1913X0 Baking Stone

Z19DD10X0 Steam set for ovens

Built-in oven with Slide&Hide® - unrestricted access to the oven interior

- $\sqrt{\ }$ Slide&Hide® unrestricted access in the oven interior and easy handling due to rotating handle
- $\sqrt{\rm CircoTherm^{\odot}}$ our smart hot-air solution for simultaneous baking and roasting on up to three levels
- $\sqrt{}$ Dual cleaning options: Pyrolytic cleaning programmes just let the oven interior clean itself. EasyClean the quick and easy option for day to day maintenance.
- $\sqrt{\,}$ LCD-Display simple, straightforward with large characters for clear reading
- $\sqrt{\text{SinglePoint MeatProbe}}$ ensures meats are cooked perfectly every time
- $\sqrt{\,}$ Clip-on Rail easily removed and installed telescopic rails for flexible use on all shelf levels

Features

Technical Data

 ${\sf Color\,/\,Material\,Front:Stainless\,steel}$

Construction type: Built-in

Integrated Cleaning system: Hydrolytic, Pyrolytic

Required niche size for installation (HxWxD) : 585-595 x 560-568 x

550

Dimensions of the product (mm) : $595 \times 594 \times 548$

Dimensions of the packed product (HxWxD) (mm): 670 x 700 x 660

Control Panel Material : Glass Door Material : Glass Net weight (kg) : 41.147 Usable volume of cavity (I) : 71

Cooking method: Bottom heat, Bread Baking Setting, Conventional

heat, Full width grill, Hot Air, Hot air grilling, Pizza setting

First cavity material : Other Oven control : electronic Number of interior lights : 1 Approval certificates : CE, VDE

Length of electrical supply cord (cm): 120

EAN code: 4242004224235 Number of cavities (2010/30/EC): 1 Energy efficiency class (2010/30/EC): A

Energy consumption per cycle conventional (2010/30/EC) : 1.04 Energy consumption per cycle forced air convection (2010/30/EC) :

0.81

Energy efficiency index (2010/30/EC) : 95.3

Connection rating (W): 2990

Current (A): 13 Voltage (V): 220-240 Frequency (Hz): 50; 60 Plug type: no plug



N 50, Built-in oven, Stainless steel B5ACM7HN0B

Features

Design

- LCD-Display Control (white)
- Enamel grey

Features

- Door lock during pyrolytic cleaning Control panel lock Automatic safety switch off Residual heat indicator
- Temperature proposal Actual temperature display Heating up indicator Sabbath setting Automatic start
- Single-point meat probe
- Interior halogen light

Cleaning

- Pyrolytic cleaning
- EasyClean

Programmes/functions

- Rapid heat
- Cooling fan

Accessories


- 1 Clip rail, Stop function
- 2 x combination grid, 1 x universal pan


Performance/technical information


- Energy efficiency rating (acc. EU Nr. 65/2014): A Energy consumption per cycle in conventional mode: 1.04 kWh Energy consumption per cycle in fan-forced convection mode: 0.81 kWh Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre
- Total connected load electric: 2.99 KW
- 120 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual

N 50, Built-in oven, Stainless steel B5ACM7HN0B

Dimensioned drawings








measurements in mm

Installation with a hob.



measurements in mm

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm